F24 - 1/2”M FULL CIRCLE LOW TRAJECTORY 12°

Undertree plastic sprinkler

Applications

Undertree irrigation in orchards and plantations, especially table grapes and bananas and any other open field irrigation in orchards.

Characteristics

- Plastic sprinkler.
- 1/2” male thread.
- Trajectory: 12°.
- Stainless steel pin and spring, effective sand protection.
- Plastic bayonet nozzles in different colours according to the diameter.
- Recommended filtration: 75mesh=200micron.

Performance table

NOZZLE colour - ø mm **ref.**	P (bar)	Q (m^3/h)	D (m)	MSH* (cm)
purple 2,5 **IDF24B0MP2500**	2,0	0,35	16,5	100
	3,0	0,43	18,5	
	4,0	0,49	20,0	
orange 2,8 **IDF24B0MP2800**	2,0	0,45	18,5	110
	3,0	0,55	20,0	
	4,0	0,63	21,0	
red 3,0 **IDF24B0MP3000**	2,0	0,51	18,5	120
	3,0	0,63	20,5	
	4,0	0,72	21,5	
green 3,2 **IDF24B0MP3200**	2,0	0,57	18,5	122
	3,0	0,70	20,5	
	4,0	0,81	22,0	
blue 3,5 **IDF24B0MP3500**	2,0	0,66	18,5	125
	3,0	0,81	20,5	
	4,0	0,93	22,0	

**MSH: Maximum height of jet over nozzle*
Data detected in laboratory conditions
Adjustments apply according to field conditions