F35 - 3/4”M FULL CIRCLE

Overhead plastic sprinkler

Applications
For overhead general use.

Characteristics
- Plastic sprinkler.
- 3/4” male thread.
- Trajectory: 25° front, 25° rear.
- Stainless steel pin and spring, effective sand protection.
- Plastic bayonet nozzles in different colours according to the diameter.
- Spacing between sprinklers: up to 20 metres.
- Recommended filtration: 75mesh=200micron.

Performance table

NOZZLE colour - ø mm **ref.**	P (bar)	Q (m^3/h)	D (m)	Precipitation (mm/h) Spacing (m) 12x15	12x18	18x18	20x20
blue 3,5 x 2,5 **IDF35C0MP3525**	3,0	1,16	26,5	6,4	5,4	-	-
	4,0	1,33	27,5	7,4	6,2	-	-
	5,0	1,47	28,0	8,2	6,8	-	-
black 4,0 x 2,5 **IDF35C0MP4025**	3,0	1,41	28,0	7,8	6,5	-	-
	4,0	1,62	29,0	9,0	7,5	-	-
	5,0	1,80	29,5	10,0	8,3	5,5	-
brown 4,5 x 2,5 **IDF35C0MP45255**	3,0	1,64	28,5	9,1	7,6	-	-
	4,0	1,90	30,0	10,6	8,8	5,9	-
	5,0	2,10	33,0	11,7	9,7	6,5	-
purple 5,0 x 2,5 **IDF35C0MP5025**	3,0	1,95	30,0	10,8	9,0	-	-
	4,0	2,25	33,5	12,5	10,4	6,9	-
	5,0	2,55	34,0	14,2	11,8	7,8	6,4
orange 5,5 x 2,5 **IDF35C0MP5525**	3,0	2,30	32,0	12,8	10,6	7,1	-
	4,0	2,65	34,5	14,7	12,3	8,2	6,6
	5,0	2,95	36,0	16,4	13,7	9,1	7,4
red 6,0 x 2,5 **IDF35C0MP6025**	3,0	2,65	33,0	14,7	12,3	8,2	6,6
	4,0	3,10	35,5	17,2	14,4	9,6	7,8
	5,0	3,45	36,0	19,2	16,0	10,6	8,6
grey 6,5 x 2,5 **IDF35C0MP6525**	3,0	3,00	34,0	-	13,9	9,3	7,5
	4,0	3,45	36,0	-	16,0	10,6	8,6
	5,0	3,85	38,0	-	17,8	11,9	9,6
grey 6,5 x 3,2 **IDF35C0MP6532**	3,0	3,20	34,0	-	14,8	9,9	8,0
	4,0	3,70	36,0	-	17,1	11,4	9,3
	5,0	4,15	38,0	-	19,2	12,8	10,4
green 7,0 x 2,5 **IDF35C0MP7025**	3,0	3,40	34,0	-	15,7	10,5	8,5
	4,0	3,90	35,0	-	18,1	12,0	9,8
	5,0	4,35	36,0	-	20,1	13,4	10,9
green 7,0 x 3,2 **IDF35C0MP7032**	3,0	3,55	34,2	-	16,4	11,0	8,9
	4,0	4,10	35,6	-	19,0	12,7	10,3
	5,0	4,60	36,0	-	21,3	14,2	11,5

Data detected in laboratory conditions
Adjustments apply according to field conditions