P34 - 3/4”M ADJUSTABLE

Overhead brass sprinkler

Applications
For overhead general use.

Characteristics
- Brass sprinkler.
- 3/4” male thread.
- Trajectory: 27°.
- Stainless steel pin and spring, effective sand protection.
- Spacing between sprinklers: up to 17 metres.
- Recommended filtration: 75mesh=200micron.

Performance table

NOZZLE ø inch - ø mm **ref.**	P (bar)	Q (m^3/h)	D (m)
9/64” 3,57 mm **IDP34C0MM0G00**	1,75	0,79	24,4
	2,10	0,89	25,0
	2,46	0,95	25,6
	2,81	1,02	26,2
	3,16	1,09	26,8
	3,51	1,16	27,4
	3,86	1,20	27,4
	4,21	1,25	28,0
5/32” 3,96 mm **IDP34C0MM0H00**	1,75	0,98	25,0
	2,10	1,07	25,6
	2,46	1,16	26,2
	2,81	1,23	26,8
	3,16	1,29	27,4
	3,51	1,36	28,0
	3,86	1,43	28,6
	4,21	1,48	28,6
11/64” 4,36 mm **IDP34C0MM0I00**	1,75	1,14	25,6
	2,10	1,25	26,2
	2,46	1,36	26,8
	2,81	1,45	27,4
	3,16	1,54	28,0
	3,51	1,64	28,6
	3,86	1,70	28,6
	4,21	1,77	29,2
3/16” 4,76 mm **IDP34C0MM0L00**	1,75	1,32	26,2
	2,10	1,45	26,8
	2,46	1,57	27,4
	2,81	1,68	28,0
	3,16	1,79	28,6
	3,51	1,91	28,6
	3,86	2,00	29,2
	4,21	2,09	29,8
13/64” 5,15 mm **IDP34C0MM0M00**	1,75	1,57	26,8
	2,10	1,73	27,4
	2,46	1,88	28,0
	2,81	2,02	28,6
	3,16	2,13	29,2
	3,51	2,25	29,8
	3,86	2,34	29,8
	4,21	2,43	30,5

Data detected in laboratory conditions
Adjustments apply according to field conditions