P35 - 3/4”M ADJUSTABLE

Overhead plastic sprinkler

Applications
For overhead general use.

Characteristics
• Plastic sprinkler.
• 3/4” male thread.
• Trajectory: 25°.
• Stainless steel pin and spring, effective sand protection.
• Plastic bayonet nozzles in different colours according to the diameter.
• Spacing between sprinklers: up to 20 metres.
• Recommended filtration: 75mesh=200micron.

Performance table

NOZZLE colour - ø mm **ref.**	P (bar)	Q (m^3/h)	D (m)
blue 3,5 **IDP35C0MP3500**	3,0	0,81	26,5
	4,0	0,93	27,5
	5,0	1,02	28,0
black 4,0 **IDP35C0MP4000**	3,0	1,06	28,0
	4,0	1,22	29,0
	5,0	1,35	29,5
brown 4,5 **IDP35C0MP4500**	3,0	1,29	28,5
	4,0	1,50	30,0
	5,0	1,65	33,0
purple 5,0 **IDP35C0MP5000**	3,0	1,60	30,0
	4,0	1,85	33,5
	5,0	2,10	34,0
orange 5,5 **IDP35C0MP5500**	3,0	1,95	32,0
	4,0	2,25	34,5
	5,0	2,50	36,0
red 6,0 **IDP35C0MP6000**	3,0	2,30	33,0
	4,0	2,70	35,5
	5,0	3,00	36,0

Data detected in laboratory conditions
Adjustments apply according to field conditions