

FLEXIFLAT™ MP

tubo Layflat monostrato in PVC appiattibile Verde

Ref.	Ø nominale	Ø interno	Spessore	Peso	Pres. max esercizio a 20°	L. bobina	Euro/m	Disp.
FLFF40050F	2"	53,0 mm	1,50 mm	0,310 kg/m	6,00 bar	100 m	2,27	●
FLFF40065F	2"½	65,0 mm	1,50 mm	0,370 kg/m	6,00 bar	100 m	2,70	●
FLFF40075F	3"	78,0 mm	1,55 mm	0,450 kg/m	4,00 bar	100 m	3,28	●
FLFF40100F	4"	105,0 mm	1,75 mm	0,630 kg/m	4,00 bar	100 m	4,45	●
FLFF40125F	5"	128,0 mm	1,75 mm	0,860 kg/m	3,00 bar	100 m	6,30	●
FLFF40150F	6"	156,5 mm	2,00 mm	1,000 kg/m	3,00 bar	100 m	7,30	●
FLFF40200F	8"	207,0 mm	2,30 mm	2,050 kg/m	2,50 bar	100 m	15,00	●



FLEXIFLAT™ HP

tubo Layflat monostrato in PVC appiattibile Verde

Ref.	Ø nominale	Ø interno	Spessore	Peso	Pres. max esercizio a 20°	L. bobina	Euro/m	Disp.
FLFF60050F	2"	53,0 mm	1,70 mm	0,330 kg/m	10,00 bar	100 m	2,65	●
FLFF60065F	2"½	65,0 mm	1,75 mm	0,400 kg/m	10,00 bar	100 m	3,21	●
FLFF6L075F	3"	78,0 mm	1,90 mm	0,570 kg/m	6,00 bar	100 m	4,56	●
FLFF60075F	3"	78,0 mm	2,10 mm	0,670 kg/m	10,00 bar	100 m	5,36	●
FLFF60090F	3"½	90,0 mm	2,20 mm	0,880 kg/m	10,00 bar	100 m	7,02	●
FLFF60100F	4"	105,0 mm	2,00 mm	0,780 kg/m	6,00 bar	100 m	6,26	●
FLFF60125F	5"	128,0 mm	2,30 mm	1,000 kg/m	6,00 bar	100 m	8,01	●
FLFF60150F	6"	156,5 mm	2,40 mm	1,500 kg/m	6,00 bar	100 m	11,71	●
FLFF60200F	8"	207,0 mm	3,00 mm	2,500 kg/m	5,00 bar	100 m	22,18	●



FLEXIFLAT™ UP

tubo Layflat monostrato in PVC appiattibile Verde

Ref.	Ø nominale	Ø interno	Spessore	Peso	Pres. max esercizio a 20°	L. bobina	Euro/m	Disp.
FLFF80040E	1"½	40,0 mm	2,00 mm	0,510 kg/m	16,00 bar	50 m	4,41	●
FLFF80050E	2"	53,0 mm	2,30 mm	0,640 kg/m	16,00 bar	50 m	5,55	●
FLFF80065E	2"½	65,0 mm	2,30 mm	0,660 kg/m	16,00 bar	50 m	5,73	●
FLFF80075E	3"	78,0 mm	2,35 mm	0,720 kg/m	16,00 bar	50 m	6,23	●
FLFF80090E	3"½	90,0 mm	2,35 mm	0,980 kg/m	16,00 bar	50 m	8,51	●
FLFF80100E	4"	105,0 mm	2,50 mm	1,100 kg/m	12,00 bar	50 m	9,56	●

